



Türk Plastik Sanayicileri Araştırma, Geliştirme ve Eğitim Vakfı

ASKIYA ALMA VE TARİFE KONTENJANINA İSTİNADEN
VERGİSİ SIFIRLANAN ÜRÜNLER

1.07.2014 tarihi itibarıyla gümrük vergisinden muaf tutulan ürünler;

- GTİP 3901 10 10 Lineer Alçak Yoğunluklu Polietilen / LLDPE (CAS No 9002-88-4) toz formunda ve aşağıdaki özelliklerde;

Komonomer ağırlığı % 5 veya daha az,
Erime akış hızı 15 g/10 min - 60 g/10 min aralığında
Yoğunluğu 0,924 g/cm³ - 0,928 g/cm³ aralığında

- GTİP 3901 90 90 Lineer Alçak Yoğunluklu Polietilen / LLDPE (CAS No 9002-88-4) toz formunda ve aşağıdaki özelliklerde;

Komonomer ağırlığı % 5, ve % 8 aralığında
Erime akış hızı 15 g/10 min - 60 g/10 min aralığında
Yoğunluğu 0,924 g/cm³ - 0,928 g/cm³ aralığında

- GTİP 3901 90 90 Yalnızca Etilen ve 1-heksen kopolimeri (CAS No 25213-02-9):

1-heksen ağırlığı %5 - %20 aralığında
Özgül ağırlığı 0,93'den az
Bir metalosen katalizörü kullanılarak üretilmiş

- GTİP 3902 90 90 Klorlu poliolefinler - çözelti ya da dispersiyon içinde olabilir

1.01.2015 tarihi itibarıyla gümrük vergisinden muaf tutulan ürünler ve Geçerlilik Süreleri

*ex 3901 10 10	10	Linear low-density polyethylene / LLDPE (CAS RN 9002-88-4) in the form of powder, with — 5 % or less by weight of comonomer, — a melt flow rate of 15 g/10 min or more, but not more than 60 g/10 min and — a density of 0,924 g/cm ³ or more, but not more than 0,928 g/cm ³	0 %	30.06.2015

Halkalı Cad. Tez-İş İş Mrk. No:132/1 Kat:4 34295 Sefaköy / İstanbul Tel.: 212 425 13 13 / 3 Hat Faks:212 624 49 26 e-mail: pagev@pagev.org.tr www.pagev.org.tr



Plast Eurasia
İstanbul 2015

Üyesi
Olduğumuz
Uluslararası
Dernekler



Plastics Europe
Association of Plastics Manufacturers



WFO WASTE FREE
OCEANS





Türk Plastik Sanayicileri Araştırma, Geliştirme ve Eğitim Vakfı

ex 3901 10 10 ex 3901 90 90	20 50	High flow linear low density polyethylene-1-butene / LLDPE (CAS RN 25087-34-7) in form of powder, with — a melt flow rate (MFR 190 °C/2,16 kg) of 16g/10min or more, but not more than 24 g/10 min and — a density (ASTM D 1505) of 0,922 g/cm ³ or more, but not more than 0,926 g/cm ³ and — a vicat softening temperature of min. 94 °C	0 %	30.06.2015
*ex 3901 90 90	30	Linear low-density polyethylene / LLDPE (CAS RN 9002-88-4) in the form of powder, with — more than 5 %, but not more than 8 % by weight of comonomer, — a melt flow rate of 15 g/10 min or more, but not more than 60 g/10 min and — a density of 0,924 g/cm ³ or more, but not more than 0,928 g/cm ³	0 %	30.06.2015
*ex 3901 90 90	40	Copolymer of ethylene and 1-hexene only (CAS RN 25213-02-9): — containing more than 5 % but not more than 20 % by weight of 1-hexene, — of a specific gravity of not more than 0,93, — manufactured using a metallocene catalyst	0 %	30.06.2015
*ex 3902 10 00	40	Polypropylene, containing no plasticiser: — of a tensile strength: of 32-60 MPa (as determined by the ASTM D638 method); — of a flexural strength of 50-90 MPa (as determined by the ASTM D790 method); — of a Melt Flow Rate (MFR) at 230 °C/ 2,16 kg of 5-15 g/10 min (as determined by the ASTM D1238 method); — with 40 % or more but not more than 80 % by weight of polypropylene, — with 10 % or more but not more than 30 % by weight of glass fibre, — with 10 % or more but not more than 30 % by weight of mica	0 %	31.12.2019

Halkalı Cad. Tez-İş İş Mrk. No:132/1 Kat:4 34295 Sefaköy / İstanbul Tel.: 212 425 13 13 / 3 Hat Faks:212 624 49 26 e-mail: pagev@pagev.org.tr www.pagev.org.tr



Plast Eurasia
İstanbul 2015

Üyesi
Olduğumuz
Uluslararası
Dernekler



PlasticsEurope
Association of Plastics Manufacturers



WFO WASTE FREE
OCEANS





Türk Plastik Sanayicileri Araştırma, Geliştirme ve Eğitim Vakfı

*ex 3902 90 90	60	Non-hydrogenated 100 % aliphatic resin (polymer), with the following characteristics: — liquid at room temperature — obtained by cationic polymerisation of C-5 alkenes monomers — with a number average molecular weight (Mn) of 370 (\pm 50) — with a weight average molecular weight (Mw) of 500 (\pm 100)	0 %	31.12.2019
*ex 3903 19 00	30	Crystalline polystyrene with a melting point of 268 °C or more but not more than 272 °C and a setting point of 232 °C or more but not more than 242 °C, whether or not containing additives and filling material	0 %	31.12.2016
*ex 3903 90 90	15	Copolymer in the form of granules containing by weight: — 78 \pm 4 % styrene, — 9 \pm 2 % n-butyl acrylate, — 11 \pm 3 % n-butyl methacrylate,, — 1.5 \pm 0,7 % methacrylic acid and — 0,01 % or more but not more than 2,5 % of polyolefinic wax	0 %	31.12.2016
*ex 3903 90 90	20	Copolymer in the form of granules containing by weight: — 83 \pm 3 % styrene, — 7 \pm 2 % n-butyl acrylate, — 9 \pm 2 % n-butyl methacrylate and — 0,01 % or more but not more than 1 % of polyolefinic wax	0 %	31.12.2016
*ex 3903 90 90	25	Copolymer in the form of granules containing by weight: — 82 \pm 6 % styrene, — 13,5 \pm 3 % n-butyl acrylate, — 1 \pm 0,5 % methacrylic acid and — 0,01 % or more but not more than 8,5 % of polyolefinic wax	0 %	31.12.2016
*ex 3904 10 00	20	Poly(vinyl chloride) powder, not mixed with any other substances or containing any vinyl acetate monomers, with: — a degree of polymerisation of 1 000 (\pm 300) monomer units, — a coefficient of heat transmission (K-value) of 60 or more, but not more than 70,	0 %	31.12.2019

Halkalı Cad. Tez-İş İş Mrk. No:132/1 Kat:4 34295 Sefaköy / İstanbul Tel.: 212 425 13 13 / 3 Hat Faks:212 624 49 26 e-mail: pagev@pagev.org.tr www.pagev.org.tr



Plast Eurasia
İstanbul 2015

Üyesi
Olduğumuz
Uluslararası
Dernekler



PlasticsEurope
Association of Plastics Manufacturers



WFO WASTE FREE
OCEANS





Türk Plastik Sanayicileri Araştırma, Geliştirme ve Eğitim Vakfı

		— a volatile material content of less than 2,00 % by weight, — a sieve non-passing fraction at a mesh width of 120 µm of not more than 1 % by weight, for use in the manufacture of battery separators (1)		
*ex 3904 50 90	92	Vinylidene-chloride methacrylate co-polymer for use in the manufacture of monofilaments (1)	0 %	31.12.2019



Üyesi
Olduğumuz
Uluslararası
Dernekler



PlasticsEurope
Association of Plastics Manufacturers



WFO WASTE FREE
OCEANS

